



Porsche Corporate Architectural Program - Setting Materials & Grout Color Specifications 2017 v 09

These grouts provide your Porsche dealership the best solution for a stain resistant grout surface. This premium grout product from AutoStone provides your dealership the best solution for cleaner floors and longevity.

ItalGraniti
New Black
Lava

Please submit to your architect for review and approval for use in your Porsche brand compliant facility.

Additionally, we have listed our recommended setting materials for use on your project. Your project may have different site conditions that may require different materials. Let us know what your site conditions require and we can revise and/or modify your setting material products.



24" x 24"

Installation Method:

- Thinset mortar installation minimum. ANSI A118.4 (polymer modified).
- Grout to be a high-performance system with stain resistant properties. Installation to be 1/8" to 3/16" width.
- Grout specification minimum: ANSI A118.7.
- See AutoStone supplied setting materials for actual product codes and grout color.

Finish: Natural

Product Code:
AS.IG.NBLava.2424.NA
(Natural).

Bullnose base
4" x 24"

Tile Specification:

Series: IGraniti.Porsche
Color: New Black Lava
Finish: Natural
Size: 24" x 24" (nominal dimension)
Thickness: 10 mm
Product Code: AS.IG.NBLava.2424.NA (Natural)

Recommended Cleaner:

Manufacturer: AutoStone Floor Systems
Product: **dealerclean**
Note: See product for dilution ratio and recommended cleaning practices.

Grout Specification:

Manufacturer: North American Adhesives
Product: AS.NA4800.EverColor.MPG
Color: AS.SmokyCoal.536
Example below: *actual color varies, example is only representative.*



Warranty:

This setting material program is backed by a Mapei (25) year setting materials system warranty. See the North American Adhesives / Mapei warranty for details, specifics and requirements.

Adhesive Specification:

Manufacturer: North American Adhesives
Product: AS.NA3800.MagnaFlex
Color: Grey

Specification Submittal:

Please use this as your reference sheet for grout specifications and our submittal for your Porsche project. If you have any questions, please contact us at:

porsche@autostoneusa.com
800-917-7027 (toll free)



Porsche Corporate Architectural Program - Setting Materials & Grout Color Specifications 2017 v 09

These grouts provide your Porsche dealership the best solution for a stain resistant grout surface. This premium grout product from AutoStone provides your dealership the best solution for cleaner floors and longevity.

Please submit to your architect for review and approval for use in your Porsche brand compliant facility.

Additionally, we have listed our recommended setting materials for use on your project. Your project may have different site conditions that may require different materials. Let us know what your site conditions require and we can revise and/or modify your setting material products.

Installation Method:

- Thinset mortar installation minimum. ANSI A118.4 (polymer modified).
- Grout to be a high-performance system with stain resistant properties. Installation to be 1/8" to 3/16" width.
- Grout specification minimum: ANSI A118.7.
- See AutoStone supplied setting materials for actual product codes and grout color.

Tile Specification:

Series: **drive**series! or **enviro**shop
Color: Alloy Grey
Finish: LINE.BR.R-12/A+B+C -or- R-Shop Textured
Size: 08"x08" -or- 12"x12" (nominal dimension)
Thickness: 9.5 mm -or- 9.8 mm
Product Code: see spec info above.

Grout Specification:

Manufacturer: North American Adhesives
Product: AS.NA4800.EverColor.MPG
Color: AS.MontanaGray.524
Example below: *actual color varies, example is only representative.*



Adhesive Specification:

Interior specification (exterior may differ on conditions)
Manufacturer: North American Adhesives
Product: AS.NA3220.Multi Flex Plus
Color: Grey

Recommended Cleaner:

Manufacturer: AutoStone
Floor Systems
Product: **dealer**clean
Note:
See product for dilution ratio and recommended cleaning practices.

Warranty:

This setting material program is backed by a Mapei (25) year setting materials system warranty. See the North American Adhesives / Mapei warranty for details, specifics and requirements.

Specification Submittal:

Please use this as your reference sheet for grout specifications and our submittal for your Porsche project. If you have any questions, please contact us as at:

porsche@autostoneusa.com
800-917-7027 (toll free)

drive

series!
Service Drive
WorkShop
Color: Alloy Grey

8" x 8"

Surface:

LINE.BRIGHT -
R-12/A+B+C

enviro

shop
WorkShop
Tech Lockers
Color: Alloy Grey

12" x 12"

Product Code:
AS.ES.AlloyGrey.1212

(Textured finish).



Porsche Corporate Architectural Program - Setting Materials & Grout Color Specifications 2017 v 09

These grouts provide your Porsche dealership the best solution for a stain resistant grout surface. This premium grout product from AutoStone provides your dealership the best solution for cleaner floors and longevity.

Please submit to your architect for review and approval for use in your Porsche brand compliant facility.

Additionally, we have listed our recommended setting materials for use on your project. Your project may have different site conditions that may require different materials. Let us know what your site conditions require and we can revise and/or modify your setting material products.

Installation Method:

- Thinset mortar installation minimum. ANSI A118.4 (polymer modified).
- Grout to be a high-performance system with stain resistant properties. Installation to be 1/8" to 3/16" width.
- Grout specification minimum: ANSI A118.7.
- See AutoStone supplied setting materials for actual product codes and grout color.

Tile Specification:

Series: **drive**series! or **enviro**shop
Color: Smoke Grey
Finish: LINE.BR.R-12/A+B+C -or- R-Shop Textured
Size: 08"x08" -or- 12"x12" (nominal dimension)
Thickness: 9.5 mm -or- 9.8 mm
Product Code: see spec info above.

Grout Specification:

Manufacturer: North American Adhesives
Product: AS.NA4800.EverColor.MPG
Color: AS.SmokyCoal.536
Example below: *actual color varies, example is only representative.*

Adhesive Specification:

Interior specification (exterior may differ on conditions)
Manufacturer: North American Adhesives
Product: AS.NA3220.Multi Flex Plus
Color: Grey

Recommended Cleaner:

Manufacturer: AutoStone
Floor Systems
Product: **dealer**clean
Note:
See product for dilution ratio and recommended cleaning practices.

Warranty:

This setting material program is backed by a Mapei (25) year setting materials system warranty. See the North American Adhesives / Mapei warranty for details, specifics and requirements.

Specification Submittal:

Please use this as your reference sheet for grout specifications and our submittal for your Porsche project. If you have any questions, please contact us as at:

porsche@autostoneusa.com
800-917-7027 (toll free)

drive

series!

Service Drive
WorkShop

Color: Smoke Grey



8" x 8"


Surface:

**LINE.BRIGHT -
R-12/A+B+C**

enviro

shop

WorkShop
Tech Lockers
Color: Smoke Grey



12" x 12"

Product Code:
AS.ES.SmokeGrey.1212

(Textured finish).



Porsche Corporate Architectural Program - Setting Materials & Grout Color Specifications 2017 v 09

These grouts provide your Porsche dealership the best solution for a stain resistant grout surface. This premium grout product from AutoStone provides your dealership the best solution for cleaner floors and longevity.

Please submit to your architect for review and approval for use in your Porsche brand compliant facility.

Additionally, we have listed our recommended setting materials for use on your project. Your project may have different site conditions that may require different materials. Let us know what your site conditions require and we can revise and/or modify your setting material products.

Installation Method:

- Thinset mortar installation minimum. ANSI A118.4 (polymer modified).
- Grout to be a high-performance system with stain resistant properties. Installation to be 1/8" to 3/16" width.
- Grout specification minimum: ANSI A118.7.
- See AutoStone supplied setting materials for actual product codes and grout color.

Tile Specification:

Series: **driveseries!** or **enviroshop**
Color: Carbon Black
Finish: LINE.BR.R-12/A+B+C -or- R-Shop Textured
Size: 08"x08" -or- 12"x12" (nominal dimension)
Thickness: 9.5 mm -or- 9.8 mm
Product Code: see spec info above.

Grout Specification:

Manufacturer: North American Adhesives
Product: AS.NA4800.EverColor.MPG
Color: AS.BlackDiamond.539
Example below: *actual color varies, example is only representative.*

Adhesive Specification:

Interior specification (exterior may differ on conditions)
Manufacturer: North American Adhesives
Product: AS.NA3220.Multi Flex Plus
Color: Grey

Recommended Cleaner:

Manufacturer: AutoStone
Floor Systems
Product: **dealerclean**
Note:
See product for dilution ratio and recommended cleaning practices.

Warranty:

This setting material program is backed by a Mapei (25) year setting materials system warranty. See the North American Adhesives / Mapei warranty for details, specifics and requirements.

Specification Submittal:

Please use this as your reference sheet for grout specifications and our submittal for your Porsche project. If you have any questions, please contact us as at:

porsche@autostoneusa.com
800-917-7027 (toll free)

driveseries!

Service Drive
WorkShop

Color: CarbonBlack



8" x 8"

Surface:

**LINE.BRIGHT -
R-12/A+B+C**

enviroshop

WorkShop
Tech Lockers
Color: CarbonBlack



12" x 12"

Product Code:
AS.ES.CarbonBlk.1212

(Textured finish).



Porsche Corporate Architectural Program - Setting Materials & Grout Color Specifications 2017 v 098

These grouts provide your Porsche dealership the best solution for a stain resistant grout surface. This premium grout product from AutoStone provides your dealership the best solution for cleaner floors and longevity.


Please submit to your architect for review and approval for use in your Porsche brand compliant facility.

Additionally, we have listed our recommended setting materials for use on your project. Your project may have different site conditions that may require different materials. Let us know what your site conditions require and we can revise and/or modify your setting material products.

Installation Method:

- Thinset mortar installation minimum. ANSI A118.4 (polymer modified).
- Grout to be a high-performance system with stain resistant properties. Installation to be 1/8" to 3/16" width.
- Grout specification minimum: ANSI A118.7.
- See AutoStone supplied setting materials for actual product codes and grout color.

ShopSeries
Color: Porsche
Shop White
walls in shop areas
Walls in Service
Shop Areas



12" x 12"

Semi-matte finish

Tile Specification:

Series: WorkShop Wall
Color: B911 White
Finish: AS.WSW.911W.1212.SemiMatte
Size: 12" x 12" (nominal dimension)
Product Code: see spec info above.

Recommended Cleaner:

Manufacturer: AutoStone Floor Systems
Product: **dealerclean**
Note: See product for dilution ratio and recommended cleaning practices.

Grout Specification:

Manufacturer: North American Adhesives
Product: AS.NA4800.EverColor.MPG
Color: NA.AspenSnow.503
Example below: *actual color varies, example is only representative.*



Warranty:

This setting material program is backed by a Mapei (25) year setting materials system warranty. See the North American Adhesives / Mapei warranty for details, specifics and requirements.

Adhesive Specification:

Interior specification (exterior may differ on conditions)
Manufacturer: North American Adhesives
Product: AS.NA3220.Multi Flex Plus
Color: Grey

Specification Submittal:

Please use this as your reference sheet for grout specifications and our submittal for your Porsche project. If you have any questions, please contact us at:

porsche@autostoneusa.com
800-917-7027 (toll free)