

Audi Terminal Wood Tile Program. Materials ASTM Schedule.

AutoStone is your Audi Architectural Terminal Program provider. Product is available from AutoStone warehouses. Order placement and shipping is on a first-come, first-serve basis. If product is out-of-stock, you may experience an extended lead-time of (4-5) weeks. Please send your pending order in so we can plan for your project and for a successful delivery. Below are ASTM specifications on this AutoStone supplied tile:

Audi Series
Color:
TechnoGrey



Sizes:
12" x 48"
8" x 48"

ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	≤0.50%	≤ 0.50%	C 373
Frost Resistance	As Reported	Resistant	C 1026
Scratch Resistance	MOHS 1-10	6.5	MOHS Scale
Breaking Strength	≥ 250 lbf.	≥ 891 lbf.	C 648
Facial Dimension	-3.0% ≤ Nominal ≤ 2.0%	Within Standard	C 499
Nominal Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C 499
Wedging (squareness)	≤ 0.25% or +/- 0.8 mm**	Within Standard	C 502
Warpage Edge (flatness)	≤ 0.40% or +/- 1.8 mm**	Within Standard	C 485
Abrasion Resistance	Class 0 - Class V	Class IV*	C 1027
Dry Coefficient of Friction	As Reported	0.70 ≤ C.O.F. < 0.80	C 1028
Wet Coefficient of Friction	As Reported	0.60 ≤ C.O.F. < 0.70	C 1028
Chemical Resistance	Class A - Class E	Class A	C 650
Stain Resistance	Class A - Class E	Class A	C 1378

* Abrasion Resistance / Suggested Applications

Class IV: Tile in this class may withstand heavier amounts of traffic with greater amounts of dirt and/or other abrasives present, including commercial kitchens and areas with regular traffic from the outside. See Coefficient of Friction and Frost Resistance for installation-specific details.

** Whichever is less

For more information email us at: audi@autostoneusa.com or call at: 214-393-4875 (Audi Hotline).