



Porsche Showroom Program. Materials ASTM Schedule.

Ital Graniti is listed vendor on the Porsche program for your showroom areas.

ItalGraniti
New Black Lava



Format
24" x 24"

Technical Characteristics	ASTM Standards	ASTM Test Results Matte	ASTM Test Methods
Water Absorption	≤0.50%	≤ 0.50%	C 373
Frost Resistance	As Reported	Resistant	C 1026
Scratch Resistance	MOHS 1-10	7	MOHS Scale
Breaking Strength	≥ 250 lbf.	≥ 850 lbf.	C 648
Facial Dimension	-3.0% < Nominal ≤ 2.0%	Within Standard	C 499
Nominal Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C 499
Wedging (squareness)	≤ 0.25% or +/- 0.8 mm**	Within Standard	C 502
Warpage Edge (flatness)	≤ 0.40% or +/- 1.8 mm**	Within Standard	C 485
Abrasion Resistance	Class 0 - Class V	Class IV*	C 1027
Dry Coefficient of Friction	As Reported	0.80 ≤ C.O.F. < 0.90	C 1028
Wet Coefficient of Friction	As Reported	0.60 ≤ C.O.F. < 0.70	C 1028
Chemical Resistance	Class A - Class E	Class A	C 650
Stain Resistance	Class A - Class E	Class A	C 1378

For more information email us at: porsche@autostoneusa.com or call at:

214-393-4875 (Porsche Hotline).