

# Clinkershop by Röben Guide Book

*2021 Edition*

---

Contains tile specifications including thickness,  
grout material matching, and more.






Light-Grey

4" x 8"  
8" x 8"  
12" x 12"



Anthracite

4" x 8"  
8" x 8"  
12" x 12"



Black-Grey

4" x 8"  
8" x 8"  
12" x 12"

## Description

The best clinker tile in the automotive industry, with licensed and proprietary AutoStone ultra-cleaning technology - brightfinish. This includes the strongest tile performance standards for workshops and service drive environments.

## Advantages

1. The best clinker choice, designed and built for automotive environments.
2. Stronger and more durable.
3. Will not permanently stain or darken when properly cleaned.
4. This product has:

**slipresistant**  
textured floor surfaces

## Manufacturer

AutoStone Floor Systems

## Uses

Evaluate for use in automotive workshop and service drive environments with high speed doors. Consult with your architect to determine dealership practices.

## DCOF

R-11 & R-12 surfaces meet the .42 DCOF rating as required for AANSI A326.3 (new standard).



## brightfinish

ultra-cleanable technology

### **Brightfinish Ultra-Cleanable Technology**

Brightfinish is a permanent sealant baked-in during kiln-firing process. The Brightfinish permanent sealant aids dealership with their cleaning practices by sealing surface micropores which trap and hold-on to rubber transfer, grease, oil or other contaminants.













### **Enhanced Impervious Surface Technology**

An impervious tile is the highest performance standard in the porcelain tile industry. The definition of an impervious tile is a surface that absorbs moisture between 0.5% to 0.001%. At AutoStone, we think that 0.5% is too much absorbency, and in an automotive dealership will cause tiles to absorb oil, grease, petroleum, gasoline and other contaminants. When this happens, your tile surface will darken over use and this leads to potential hazards such as STF (slip, trip and fall) events. Petroleum and oils soaked surfaces can pose other hazards when not properly removed with regularly scheduled and proper cleaning practices. With the addition of our brightfinish we enhance our impervious tiles and reduce their absorbency to levels at the lowest end of the spectrum (0.001% or less). This means nothing is absorbed by an AutoStone workshop or service drive floor tile. AutoStone workshop floor systems are premium floor systems which are designed to resist staining and be easier to clean.

### **Limitations**

Surface is a non-vitreous (impervious) enhanced porcelain tile. Oil, grease and all contaminants will remain on surface until properly cleaned and removed.

*Not for use in carwash areas where high volume water and/or high pressure water systems are used.*

clinkershop in partnership with Röben	THICKNESS		LIGHT-GREY	ANTHRACITE	BLACK-GREY
	METRIC DIMENSIONS	U.S. NOMINAL DIMENSIONS			
<b>4" x 8"</b> R-10   R-11 and R-12		<b>5/8"</b>			
<b>8" x 8"</b> R-10   R-11 and R-12		<b>5/8"</b>			
<b>12" x 12"</b> R-9 and R-10		<b>5/8"</b>			

\* thickness tolerance is: (+) or (-) .5mm

## Clinkershop by Röben Sizes & Thicknesses in Metric & U.S. Nominal

\*thickness tolerance is (+) or (-) .5mm

Light-Grey	Anthracite	Black-Grey
4" x 8" -15mm (5/8")	4" x 8" -15mm (5/8")	4" x 8" -15mm (5/8")
8" x 8" -15mm (5/8")	8" x 8" -15mm (5/8")	8" x 8" -15mm (5/8")
12" x 12" -15mm (5/8")	12" x 12" -15mm (5/8")	12" x 12" -15mm (5/8")

With multiple floor surfaces and thicknesses AutoStone Floor Systems has the right floor solution for your unique situation.

**Visit [AutoStoneUSA.com](https://autostoneusa.com) today.**



4" x 8"



8" x 8"



12" x 12"

	R-11	Stocked EU	■ Light-Grey	R-11	Stocked EU	■ Light-Grey	R-9	Standard 8-10	■ Light-Grey
		Stocked EU	■ Anthracite		Stocked EU	■ Anthracite	R-10	Standard 8-10	■ Anthracite
		Stocked EU	■ Black-Grey		Stocked EU	■ Black-Grey		Standard 8-10	■ Black-Grey
	R-10	Standard 8-10	■ Light-Grey	R-10	Standard 8-10	■ Light-Grey	R-11	Non-Standard	■ Light-Grey
	R-12	Standard 8-10	■ Anthracite	R-12	Standard 8-10	■ Anthracite		Non-Standard	■ Anthracite
		Standard 8-10	■ Black-Grey		Standard 8-10	■ Black-Grey		Non-Standard	■ Black-Grey

\* thickness tolerance is: (+) or (-) .5mm

## Material Availability

- STOCKED EU | Product stocked at factory in EU. 1-2 week preparation + 4 week shipping.
- STANDARD 8-10 | Standard production product. 8-10 week production + 4 week shipping.
- NON-STANDARD | Minimum quantities may be required. 8-10 week production + 4 week shipping.



## Installation

See AutoStone recommended 09300 specifications for thinset standards on concrete substrate and AutoStone recommended installation standards.

## Recommended Grout Color & Setting Materials by Laticrete

### Light-Grey

**Grout:** Laticrete Permacolor 89 Smoke Grey

**Thinset:** LHT Plus

Below: actual color varies, example is only representative



### Anthracite

**Grout:** Laticrete Permacolor 42 Platinum

**Thinset:** LHT Plus

Below: actual color varies, example is only representative



### Black-Grey

**Grout:** Laticrete Permacolor 45 Raven

**Thinset:** LHT Plus

Below: actual color varies, example is only representative

